

- For more records, click the Records link at page end.
- To change the format of selected records, select format and click Display Selected.
- To print/save clean copies of selected records from browser click Print/Save Selected.
- To have records sent as hardcopy or via email, click Send Results.

<input checked="" type="checkbox"/> Select All	Format
<input checked="" type="checkbox"/> Clear Selections	Print/Save Selected
<input checked="" type="checkbox"/> Send Results	Display Selected <input style="border: 1px solid black; padding: 2px 10px; margin-left: 10px;" type="button" value="Free"/>

1. 1/5/1

012779510

WPI Acc No: 99-585736/199950

XRAM Acc No: C93-170781

Glass with after-glow - used in the manufacture of
photo-preserving glass

Patent Assignee: HIRAO K (HIRA-I); KAGAKU GIJUTSU SHINKO JIGYODAN (KAGA-N);
NEMOTO TOKUSHU KAGAKU KK (NEMO-N)

Number of Countries: 001 Number of Patents: 001

Patent Family:

Patent No	Kind	Date	Applicat No	Kind	Date	Main IPC	Week
JP 11255536	A	19990921	JP 9860936	A	19980312	C03C-004/12	199950 B

Priority Applications (No Type Date): JP 9860936 A 19980312

Patent Details:

Patent	Kind	Lat	Pg	Filing Notes	Application	Patent
JP 11255536	A		9			

Abstract (Basic): JP 11255536 A

(1) A glass composition (A) mainly composed of at least one compound (B) of CaO and SrO and at least one compound (C) of (Al2O3), (B2O3), and (SiO2). (A) also contg. 0.001-10 molar % of (Eu) as activating agent (D) and 0.001-10 molar % of at least one of Nd, Sm, Gd, Tb, Dy, Ho, Er, Tm, Yb, and Lu as co-activating agent (E). (2) (A) in (1), mainly composed of (B), (C), 0.001-10 molar % of (Eu), and 0.001-10 molar % of at least one of Nd and Dy as co-activating agent.

(3) (A) in (1), mainly composed of CaO, Al2O3, and SiO2, contg. 0.001-10 molar % of (Eu) as (D) and 0.001-10 molar % of Nd as (E). (4)

(A) in (1), mainly composed of SrO, Al2O3, and SiO2, also contg.

0.001-10 molar % of (Eu) as (D) and 0.001-10 molar % of Dy as (E). (5)

(A) in (1), mainly composed of CaO, Al2O3, and B2O3, also contg.

0.001-10 molar % of (Eu) as (D) and 0.001-10 molar % of Dy as (E).

USE - Used as the glass with after glow.

ADVANTAGE - This method is able to manufacture photo-preserving glass.

Dwg. 0/14

Title Terms: GLASS; AFTER; GLOW; MANUFACTURE; PHOTO; PRESERVE; GLASS

Derwent Class: L01

International Patent Class (Main): C03C-004/12

File Segment: CPI